



# FLEXIBLE AIR DUCT HOSE

**PRODUCT TYPE:** AIR AND DEFROSTER SYSTEMS

**RECOMMENDED FOR:** Connections between hot air sources with air cleaners or other aggregates. After being formed; it retains its original shape.

**RESISTANT TO:** Resistant to the harmful conditions under the bonnet; heat, ozone and coolant additives.

**CONSTRUCTION:**

**SHAPE:** Straight

**TUBE:** Aluminum

**REINFORCEMENT:** -

**WIRE:** -



**COVER:** -

**STANDARDS:**

**SAE NORM** -

**DIN NORM** -

**TEMPERATURE:**



Gates	PN	↔		∅	↔	↔	⌚
		mm	"	mm	m	m	bar
FD19X0.5	7743-00519	19	3/4	20	0.5	0.2	0.2
FD19X1	7743-01019	19	3/4	20	1	0.4	0.2
FD22X0.5	7743-00522	22	7/8	23	0.5	0.2	0.2
FD22X1	7743-01022	22	7/8	23	1	0.4	0.2
FD25X0.5	7743-00525	25	1	26	0.5	0.2	0.2
FD25X1	7743-01025	25	1	26	1	0.4	0.2
FD35X1	7743-01035	35	1 3/8	36	1	0.4	0.2
FD38X0.5	7743-00538	38	1 1/2	39	0.5	0.2	0.2
FD38X1	7743-01038	38	1 1/2	39	1	0.4	0.2
FD40X0.5	7743-00540	40	1 9/16	41	0.5	0.2	0.2
FD40X1	7743-01040	40	1 9/16	41	1	0.4	0.2
FD45X0.5	7743-00545	45	1 3/4	46	0.5	0.2	0.2
FD45X1	7743-01045	45	1 3/4	46	1	0.4	0.2
FD50X0.5	7743-00550	50	2	51	0.5	0.2	0.2
FD50X1	7743-01050	50	2	51	1	0.4	0.2
FD52X1	7743-01052	52	2	53	1	0.4	0.2
FD52X1.3	7743-01352	52	2	53	1.3	0.545	0.2
FD55X0.5	7743-00555	55	2 1/5	56	0.5	0.2	0.2
FD55X1	7743-01055	55	2 1/5	56	1	0.4	0.2
FD60X0.5	7743-00560	60	2 3/8	61	0.5	0.2	0.2
FD60X1	7743-01060	60	2 3/8	61	1	0.4	0.2